




Installation Method



Ashlar

Herringbone

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see www.interface.com/disclaimer.

Product Crossroads **Colour** Stepping Stone **Collection** Earthen Forms Collection

Product Specifications

Product Number	A034
Product Construction	High Performance Luxury Vinyl Tile contains 39% Pre-Consumer Recycled Content
Finish	Ceramor+™ UV stabilised Ceramic Bead Coating
Wear Layer Thickness	(EN ISO 24340) 0.55 mm
Total Thickness	(EN ISO 24346) 4.5 mm
Total Weight	6,880 g/m²
Size	25cm x 1m
Tiles per Box	10 - 2.5m²
Backing	Sound Choice™ Acoustic Backing

Performance Specifications

Wear Classification	EN ISO 10874 33 Heavy Commercial / 42 General Light Industrial
CE Declaration Of Performance	DOP PBRG-AHCK3R
UKCA Declaration of Performance	DOP PBRG-AHCK3R
Castor Chair Rating	(ISO 4918 / EN425) Pass
Flammability	(EN ISO 9239-1) Euroclass Bfl-s1 (EN 13501-1)
Light Fastness	≥7 (ISO 105-B02)
Light Reflectance Value (LRV-L)	52.43
Light Reflectance Value (LRV-Y)	20.52
Dimensional Stability	(ISO 23999) ≤ 0.25 %
Curling	≤ 2 mm (ISO 23999)
Flexibility	(EN ISO 24344) Method A - Pass
Abrasion Resistance	(EN 660-2) Group T
Residual Indentation	(EN ISO 24343-1) ≤ 0.2 mm
Determination of Anti-Slip	R10 (EN 16165 - Annex B)
Pendulum Wet & Dry 4S	36+ Low slip potential (EN 16165 - Annex C)
Chemical Resistance	(EN ISO 26987) Very Good
Impact Sound Insulation ΔLw EN ISO 10140-3	16 dB

Environmental Specifications

Environmental Product Declaration	Download EPD
Disclosure of Product Ingredients	Health Product Declaration
Total Recycled Content	39 %
Indoor Air Quality	French A+ Indoor Air Comfort GOLD® LVT Greenguard Gold M1 Emission Certification - LVT
Embodied Carbon (Cradle to Gate)	9.2 kg CO ₂ eq./m²
Material Composition	Free of Ortho Phthalates

Technical Information

Installation	See recommended LVT installation guidelines
Maintenance	See recommended LVT maintenance guidelines
Warranty	15 years LVT

Certifications



0.03



16 dB

[illegible]

21

Interface Company Manufacturing B.V.
Informatie 15
0095 BD
Schippenholweg
The Netherlands

DCEFBMS - AJRCRI

EN 14041:2004
Approved Body - DGS

Resistor heat convection measurements.
Class:exp1 Class ID:1 (See EN 10876)
Reaction to fire Class ID:1 (See EN 14041, clause 4.3)
Oily resistance Class ID:5 (See EN 14041, clause 4.3)
Form stability ID: See EN 14041, clause 4.3)
Air transport < 200g (See EN 14041, clause 4.3.1)

www.interface.com/en-us